





horizontal  
**6626** 960\_961\_962



6626 960 314	10,3W.	1.405	136,4lm/W.	spot	3.000
6626 960 324	10,3W.	1.405	136,4lm/W.	medium	3.000
6626 960 338	10,3W.	1.405	136,4lm/W.	flood	3.000
6626 960 414	10,3W.	1.486	144,3lm/W.	spot	4.000
6626 960 424	10,3W.	1.486	144,3lm/W.	medium	4.000
6626 960 438	10,3W.	1.486	144,3lm/W.	flood	4.000
6626 961 314	16,8W.	2.422	144,2lm/W.	spot	3.000
6626 961 324	16,8W.	2.422	144,2lm/W.	medium	3.000
6626 961 338	16,8W.	2.422	144,2lm/W.	flood	3.000
6626 961 414	16,8W.	2.526	150,4lm/W.	spot	4.000
6626 961 424	16,8W.	2.526	150,4lm/W.	medium	4.000
6626 961 438	16,8W.	2.526	150,4lm/W.	flood	4.000
6626 962 314	25,4W.	3.637	143,2lm/W.	spot	3.000
6626 962 324	25,4W.	3.637	143,2lm/W.	medium	3.000
6626 962 338	25,4W.	3.637	143,2lm/W.	flood	3.000
6626 962 414	25,4W.	3.785	149lm/W.	spot	4.000
6626 962 424	25,4W.	3.785	149lm/W.	medium	4.000
6626 962 438	25,4W.	3.785	149lm/W.	flood	4.000

code module W lm efficiency beam angle °K

colores\_colors

1 3 8

materiales\_materials

aluminio inyectado  
die cast aluminium

pedido\_order

6626	960	4	14	8
code	10,3W	°K	beam angle	color





| *horizontal*  
**6626** 960\_961\_962

*horizontal*



**6611**



en la imagen\_in the picture