



7000
7058 960_961



7058 960 314	10,3W.	1.405	136,4lm/W.	spot	3.000
7058 960 324	10,3W.	1.405	136,4lm/W.	medium	3.000
7058 960 338	10,3W.	1.405	136,4lm/W.	flood	3.000
7058 960 414	10,3W.	1.486	144,3lm/W.	spot	4.000
7058 960 424	10,3W.	1.486	144,3lm/W.	medium	4.000
7058 960 438	10,3W.	1.486	144,3lm/W.	flood	4.000
7058 961 314	16,8W.	2.422	144,2lm/W.	spot	3.000
7058 961 324	16,8W.	2.422	144,2lm/W.	medium	3.000
7058 961 338	16,8W.	2.422	144,2lm/W.	flood	3.000
7058 961 414	16,8W.	2.526	150,4lm/W.	spot	4.000
7058 961 424	16,8W.	2.526	150,4lm/W.	medium	4.000
7058 961 438	16,8W.	2.526	150,4lm/W.	flood	4.000
code	module W	lm	efficiency	beam angle	°K

colores_colors



materiales_materials

aluminio inyectado
die cast aluminium



pedido_order

7058	960	4	14	8
code	10,3W	°K	beam angle	color



7000

7068



ledline

7211



ledline

7122



en la imagen_in the picture




| 7000
7058 960_961

7000

7839



en la imagen_in the picture



| 7000
7058 960_961

7000

7616



en la imagen_in the picture