





sie7e
7843 960_961_962



code	module W	lm	efficiency	beam angle	°K
7843 960 314	2x10,3W	2x1.405	136,4lm/W.	spot	3.000
7843 960 324	2x10,3W	2x1.405	136,4lm/W.	medium	3.000
7843 960 338	2x10,3W	2x1.405	136,4lm/W.	flood	3.000
7843 960 414	2x10,3W	2x1.486	144,3lm/W.	spot	4.000
7843 960 424	2x10,3W	2x1.486	144,3lm/W.	medium	4.000
7843 960 438	2x10,3W	2x1.486	144,3lm/W.	flood	4.000
7843 961 314	2x16,8W	2x2.422	144,2lm/W.	spot	3.000
7843 961 324	2x16,8W	2x2.422	144,2lm/W.	medium	3.000
7843 961 338	2x16,8W	2x2.422	144,2lm/W.	flood	3.000
7843 961 414	2x16,8W	2x2.526	150,4lm/W.	spot	4.000
7843 961 424	2x16,8W	2x2.526	150,4lm/W.	medium	4.000
7843 961 438	2x16,8W	2x2.526	150,4lm/W.	flood	4.000
7843 962 314	2x25,4W	2x3.637	143,2lm/W.	spot	3.000
7843 962 324	2x25,4W	2x3.637	143,2lm/W.	medium	3.000
7843 962 338	2x25,4W	2x3.637	143,2lm/W.	flood	3.000
7843 962 414	2x25,4W	2x3.785	149lm/W.	spot	4.000
7843 962 424	2x25,4W	2x3.785	149lm/W.	medium	4.000
7843 962 438	2x25,4W	2x3.785	149lm/W.	flood	4.000

colores_colors



materiales_materials

aluminio inyectado
y acero
die cast aluminium
and steel

pedido_order

7843	960	4	14	8
code	10,3W	°K	beam angle	color



sie7e

7171



en la imagen_in the picture




| sie7e
7843 960_961_962

sie7e

7175



en la imagen_in the picture



| sie7e
7843 960_961_962

sie7e

7139



en la imagen_in the picture