





easy  
**8957** 931\_932\_933\_934



8957 931 300	13,9W.	1.320	95lm/W.	-	3.000
8957 931 400	13,9W.	1.390	100lm/W.	-	4.000
8957 932 300	23,6W.	2.260	96lm/W.	-	3.000
8957 932 400	23,6W.	2.380	101lm/W.	-	4.000
8957 933 300	31W.	3.270	105lm/W.	-	3.000
8957 933 400	31W.	3.450	111lm/W.	-	4.000
8957 934 300	51,7W.	5.880	113,7lm/W.	-	3.000
8957 934 400	51,7W.	6.200	119,9lm/W.	-	4.000
code	module W	lm	efficiency	beam angle	°K

CEILING CUT  
136x136



colores\_colors



materiales\_materials

aluminio inyectado  
y acero  
die cast aluminium  
and steel

accesorios\_accesories



0  
vidrio opal  
opal glass



1  
vidrio prismático  
prismatic glass



easy

**8946**



en la imagen\_in the picture



| easy  
**8957** 931\_932\_933\_934



easy



**8619**

iSpot



**5003**

ilutrac



**3011NK**

en la imagen\_in the picture



| easy  
**8957** 931\_932\_933\_934

easy



**8946**



en la imagen\_in the picture