




iBlock
5124 26_977



5124 977 310	10W.	1.100	110lm/W.	spot	3.000
5124 977 320	10W.	1.100	110lm/W.	spot	3.000
5124 977 336	10W.	1.100	110lm/W.	medium	3.000
5124 977 360	10W.	1.100	110lm/W.	flood	3.000
5124 977 410	10W.	1.100	110lm/W.	spot	4.000
5124 977 420	10W.	1.100	110lm/W.	spot	4.000
5124 977 436	10W.	1.100	110lm/W.	medium	4.000
5124 977 460	10W.	1.100	110lm/W.	flood	4.000
5126 977 310	27W.	2.500	92,6lm/W.	spot	3.000
5126 977 320	27W.	2.500	92,6lm/W.	spot	3.000
5126 977 336	27W.	2.500	92,6lm/W.	medium	3.000
5126 977 360	27W.	2.500	92,6lm/W.	flood	3.000
5126 977 410	27W.	2.500	92,6lm/W.	spot	4.000
5126 977 420	27W.	2.500	92,6lm/W.	spot	4.000
5126 977 436	27W.	2.500	92,6lm/W.	medium	4.000
5126 977 460	27W.	2.500	92,6lm/W.	flood	4.000


code	module W	lm	efficiency	beam angle	°K
------	----------	----	------------	------------	----

colores_colors



materiales_materials

aluminio inyectado
y acero
die cast aluminium
and steel



CASAMBI
COMPATIBLE

opciones_options

-	base	5124 977 310
B	3 fases_phase	5124 977 310B

