




sie7e

**7840** 960\_961\_962



code	module W	lm	efficiency	beam angle	°K
7840 960 314	10,3W.	1.405	136,4lm/W.	spot	3.000
7840 960 324	10,3W.	1.405	136,4lm/W.	medium	3.000
7840 960 338	10,3W.	1.405	136,4lm/W.	flood	3.000
7840 960 414	10,3W.	1.486	144,3lm/W.	spot	4.000
7840 960 424	10,3W.	1.486	144,3lm/W.	medium	4.000
7840 960 438	10,3W.	1.486	144,3lm/W.	flood	4.000
7840 961 314	16,8W.	2.422	144,2lm/W.	spot	3.000
7840 961 324	16,8W.	2.422	144,2lm/W.	medium	3.000
7840 961 338	16,8W.	2.422	144,2lm/W.	flood	3.000
7840 961 414	16,8W.	2.526	150,4lm/W.	spot	4.000
7840 961 424	16,8W.	2.526	150,4lm/W.	medium	4.000
7840 961 438	16,8W.	2.526	150,4lm/W.	flood	4.000
7840 962 314	25,4W.	3.637	143,2lm/W.	spot	3.000
7840 962 324	25,4W.	3.637	143,2lm/W.	medium	3.000
7840 962 338	25,4W.	3.637	143,2lm/W.	flood	3.000
7840 962 414	25,4W.	3.785	149lm/W.	spot	4.000
7840 962 424	25,4W.	3.785	149lm/W.	medium	4.000
7840 962 438	25,4W.	3.785	149lm/W.	flood	4.000

colores\_colors

1 3 8

materiales\_materials

aluminio inyectado y acero  
die cast aluminium and steel

LED IP20 INCL. 350° 30°

pedido\_order

7840	960	4	14	8
code	10,3W	°K	beam angle	color



sie7e

7171



en la imagen\_in the picture



| sie7e  
**7840** 960\_961\_962


sie7e



7175



en la imagen\_in the picture



| sie7e  
**7840** 960\_961\_962

sie7e

**7139**



en la imagen\_in the picture