






cardanLED111  
**8613** 960\_961\_962\_963



CASAMBI  
 COMPATIBLE

8613 960 314	10,3W.	1.405	136,4lm/W.	spot	3.000
8613 960 324	10,3W.	1.405	136,4lm/W.	medium	3.000
8613 960 338	10,3W.	1.405	136,4lm/W.	flood	3.000
8613 960 414	10,3W.	1.486	144,3lm/W.	spot	4.000
8613 960 424	10,3W.	1.486	144,3lm/W.	medium	4.000
8613 960 438	10,3W.	1.486	144,3lm/W.	flood	4.000
8613 961 314	16,8W.	2.422	144,2lm/W.	spot	3.000
8613 961 324	16,8W.	2.422	144,2lm/W.	medium	3.000
8613 961 338	16,8W.	2.422	144,2lm/W.	flood	3.000
8613 961 414	16,8W.	2.526	150,4lm/W.	spot	4.000
8613 961 424	16,8W.	2.526	150,4lm/W.	medium	4.000
8613 961 438	16,8W.	2.526	150,4lm/W.	flood	4.000
8613 962 314	25,4W.	3.637	143,2lm/W.	spot	3.000
8613 962 324	25,4W.	3.637	143,2lm/W.	medium	3.000
8613 962 338	25,4W.	3.637	143,2lm/W.	flood	3.000
8613 962 414	25,4W.	3.785	149lm/W.	spot	4.000
8613 962 424	25,4W.	3.785	149lm/W.	medium	4.000
8613 962 438	25,4W.	3.785	149lm/W.	flood	4.000
8613 963 314	41,5W.	5.772	139lm/W.	spot	3.000
8613 963 324	41,5W.	5.772	139lm/W.	medium	3.000
8613 963 338	41,5W.	5.772	139lm/W.	flood	3.000
8613 963 414	41,5W.	6.088	146,7lm/W.	spot	4.000
8613 963 424	41,5W.	6.088	146,7lm/W.	medium	4.000
8613 963 438	41,5W.	6.088	146,7lm/W.	flood	4.000

code module W lm efficiency beam angle °K

colores\_colors



materiales\_materials

aluminio inyectado  
 y acero  
 die cast aluminium  
 and steel

pedido\_order

8613	960	4	14	8
code	10,3W	°K	beam angle	color



cardanLED111



8068

en la imagen\_in the picture



cardanLED111  
**8613** 960\_961\_962\_963

cardanLED111



**8069**



en la imagen\_in the picture





cardanLED111  
**8613** 960\_961\_962\_963



cardanLED111  
**8613**

en la imagen\_in the picture



cardanLED111  
**8613**

en la imagen\_in the picture